

SO-WB001/EU

NEW BORA POWER EXTERNAL SOUNDER



FIRE & SECURITY

- High power external siren and strobe 120dB @ 1mtr
- High security - Double skinned housing:
External: UV stable ABS 3mm Plastic
Internal: 0.8mm Galvanized metal cover.
- Modulated two tone sound output
- High intensity LED strobe
- 3 Way tamper protection – screw, cover and back
- Positive and negative alarm trigger input
- Negative trigger input to activate the LED strobe only
- Selectable siren timer can be set as to follow trigger input (continuous) or 3 minutes cut-off
- Selectable Comfort LEDS (scrolling or off)
- Power failure alarm
- Protection against total battery discharge
- Blue lens available

Specifications

<i>Sounder volume</i>	120(A)db @ 1 mtr	<i>Input impedance</i>	1K ohm
<i>Siren tone</i>	Two tone	<i>Tamper switch</i>	Cover
<i>Frequency range</i>	1300-2400Hz	<i>Battery type</i>	Rechargeable lead acid 12VDC *
<i>Strobe</i>	High intensity LED	<i>Low battery monitor</i>	8VDC +/- 0.3VDC
<i>Power supply</i>	13.8 ~ 14.2v DC	<i>Housing</i>	External: ABS Internal: Galvanized metal
<i>Charge current limit</i>	250mA	<i>Size</i>	W: 190mm H: 275mm D: 95mm
<i>Current consumption</i>	Standby: 8mA Alarm: 1600mA@13.8VDC	<i>Weight</i>	1.85Kg (without battery)
<i>Maximum power output</i>	50W (peak)	<i>Temperature range</i>	-30°C to +60°C
<i>Trigger level</i>	Low = Max. 1VDC High = Min. 9VDC	<i>Lens Option</i>	BCAD/LENS/BL - Interchangeable blue lens
<i>Siren timer options</i>	Continuous (set by panel) / 3 Minutes		

* Requires 12vdc rechargeable battery, 2.3 or 7ApH

Contact us:

Phone:

Tel: +44(0)151 6061000

Fax: +44(0)151 6061122

Online:

Web: www.cqr.co.uk

Email: info@cqr.co.uk



Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

